

Exterior Masonry Textured Basecoat



Emperor® Textured Basecoat is a silicone-based exterior textured coating for creating a range of textured finishes on exterior rendered surfaces.

Preparation: All surfaces must be dry, clean, sound and free of contaminants. Cracks and holes greater than 0.5mm need to be repaired with a suitable masonry filler. Allow any filler to dry thoroughly for minimum 24 hours. Emperor Textured Basecoat is self-priming and does not require a primer.

Application: Thoroughly stir before use. Apply using a paint brush or paint roller. Using either a light, medium or rough textured roller will help create different finishes. Apply generously with a full brush or roller and avoid spreading too thinly.

Recommended for: Any bare or previously painted masonry and render, including brick, stone, cement and silicone-based render, where a textured finish is required.

Colour: White

Coverage rate: Approx. 350–500 g/m² per coat – depending on substrate and application method.

Drying time: Touch dry in up to 4 hours 20°C. Recoatable in 24 hours at 20°C. Lower temperatures and higher humidity extend the drying time accordingly.

Application Conditions: Minimum temperature 5°C. Relative humidity should not exceed 65%.

Storage: Must be stored in dry, frost free conditions preferably at room temperature.

Shelf life: Minimum 2 years (in original sealed container).

Cleaning: Clean equipment with warm soapy water.

Overcoating: Must be overcoated with two-coats of Emperor Masonry Paint.

Thinning: Do not dilute.



*when applied in accordance with the manufacturer's data sheet

To purchase Emperor Paint and associated accessories such as cleaner, textured basecoat and other items, please visit:

www.emperorpaint.co.uk

Unit 32, Peel Industrial Estate,
Chamberhall Street, Bury,
Lancashire, BL9 0LU

info@emperorpaint.co.uk

**Tested & approved by the world's
leading scientists**